### Application S-7180AT-91 P

## S-7180A-81 P

Application
Application

3 Medium materials Heavy materials

	0.450 / 0.450
-913P / -813P	-915P / -815P
5,000sti/min	4,000sti/min
3,200sti/min	
5mm	5mm*
Double action thread trimming mechanism	
Standard equipment	
Knee lifter:10~15mm / Auto foot lifter:12mm	
#11-#18	#19-#22
0.9mm	1.2mm
AC servo motor	
37kg	
Single-phase:200~240V Max. electric power consumption 400VA	
	5,000sti/min  3,200 5mm  Double action thread Standard Standard Standard Standard Standard Knee lifter:10~15mm #11-#18 0.9mm  AC serv

<sup>\*</sup> If you need 7mm specification, please contact our sales representative.





S-7180A

S-7180AT



**Brother GT/ISM Support App** 


















-Photographs are for illustration purpose. They may not represent actual operating conditions and may display optional parts.

**BROTHER MACHINERY SHANGHAI LTD.** BROTHER MACHINERY (ASIA) LTD. ASIA

**EUROPE** BROTHER INTERNATIONALE INDUSTRIEMASCHINEN GmbH https://www.brother-ism.com/ **AMERICAS BROTHER INTERNATIONAL CORPORATION** 

https://www.brother.cn/ https://www.brother.com.hk/

https://www.brother-usa.com/

+86-21-3135-3355 +852-2777-0010 +49-2822-6090

+1-908-704-1700

Working with you for a better environme



1-5, Kitajizoyama, Noda-cho, Kariya-shi, Aichi 448-0803, Japan. Phone: 81-566-95-0088 Fax: 81-566-25-3721 https://industrialsewingmachine.global.brother/



# S-7180AT S-7180A

Single Needle Direct Drive Straight Lock Stitcher with Thread Trimmer, **Electric Feeding System and Auto Foot Lifter** 

With direct drive motor, Auto foot lifter and stitch length control, this machine offers beautiful sewing quality and high producibility.

- New Electric Feed System
- Short remaining thread (3.5mm)
- Auto Foot Lifter
- Sealed oil tank equipped



**Advance & Convenience** 


## **Advance & Convenience**

With direct drive motor, auto foot lifter and stitch length control, this machine offers beautiful sewing quality and high producibility.


## **New Electric Feed System**


Equipped with pulse motor. It is possible to set the stitch length as a numerical value with this panel which has easy-to-understand key layout.

S-7180AT: Color LCD touch Panel



S-7180A: Standard Panel







The double action thread trimming mechanism cut's the thread right under the needle hole, realizing the short remaining thread at minimum of 3.5mm. In addition, using the beautiful mode to enhances the beautiful sewing end.



Conventional





## **Auto Foot Lifter**

Productivity improvement and quietness are realized by this equipment.

**Sealed Oil Tank Equipped** 

The sealed tank is equipped same as S-7250A.



## **LED Light Equipped as Standard**

Both-sides of the LED handy light are equipped as standard for better operation, preventing shadows on the garment.



